

Input data

System of measurement		Metric
Input type		Gear motor
Input speed	[rpm]	1400
Output speed	[rpm]	71.28
Ratio (i=)		19.64
Frequency	[Hz]	50
Input options		IEC
Requested input power	[kW]	5.5
Service factor		0.9
Rated Power P1	[kW]	5.05

Output data

Gear unit	M RD 42 B3 H1 19.64 132 B14 AU 35x70 MT 5.5 kW 132 S4 B14 X3
------------------	---

Type		RD - Helical gearboxes
Input type		M
Size		42
Ratio (i=)		19.64
Input flange		B14
Mounting position		H1
Input speed	[rpm]	1400
Output speed	[rpm]	71.28
Rated output torque	[Nm]	707.38
Service Factor		0.9
Efficiency		0.96
Inertia moment	[kgm ²]	0.000819

Gear unit configuration

Fixing		Feet
Output shaft		AU 35x70

Output radial and axial loads


Output radial load	[N]	5800
Output axial load	[N]	1160

Electric motor

Size		132 S4
Poles		4
Power	[kW]	5.5


Electric motor configuration

Motor flange		B14
Terminal box position		X3




M RD 42 B3 H1 19.64 132 B14 AU 35x70 MT 5.5 kW 132 S4 B14 X3

Mounting positions



Lubricant type: Long life synthetic oil ISO VG320

Direction of rotation



Weight

Gear unit [kg]	20
Electric motor [kg]	43

M RD 42 B3 H1 19.64 132 B14 AU 35x70 MT 5.5 kW 132 S4 B14 X3