

Input data

System of measurement		Metric
Input type		Gear motor
Input speed	[rpm]	1400
Output speed	[rpm]	93.33
Ratio (i=)		15
Frequency	[Hz]	50
Input options		IEC
Requested input power	[kW]	1.5
Service factor		1
Rated Power P1	[kW]	1.57

Output data

Gear unit	M RT 60 B3 15 90 B14 AC 25 MT 1.5 kW 90 L4 B14 X3
------------------	--

Type		RT - Worm speed reducers
Input type		M
Size		60
Ratio (i=)		15
Input flange		B14
Input speed	[rpm]	1400
Output speed	[rpm]	93.33
Rated output torque	[Nm]	124.32
Service Factor		1
Efficiency		0.81
Inertia moment	[kgm ²]	0.00011

Gear unit configuration

Output shaft		Hollow output shaft
Fixing		Universal
Version		B3

Output radial and axial loads

Ball bearings output radial load	[N]	2900
Taper bearings output radial load	[N]	3700
Ball bearings output axial load	[N]	580
Taper bearings output axial load	[N]	740

Accessories





Hollow output shaft		AC 25
---------------------	--	-------

Electric motor



Size		90 L4
Poles		4
Power	[kW]	1.5

Electric motor configuration


Motor flange		B14
Terminal box position		X3




Hollow output shaft



Mounting positions



Terminal box position



0.23



Oil quantity [litres]

Lubricant type: Long life synthetic oil ISO VG320

Direction of rotation



Weight

Gear unit [kg]	6.5
Electric motor [kg]	13.5

Gearing data

Axial module	3.1
Number of starts	2
Lead angle	12° 55'
Pressure angle	20°

Backdriving

Static back-driving
Quick back-driving
Dynamic back-driving

M RT 60 B3 15 90 B14 AC 25 MT 1.5 kW 90 L4 B14 X3